


SIZE	A	B	C	D	F	G	H	W	ACT.
1/4	167	146	30.5	16	67	33.5	192.5	96	U0
3/8	167	146	30.5	16	67	33.5	192.5	96	U0
1/2	167	146	38.0	16	75	33.5	200.0	96	U0
3/4	167	146	40.5	20	80	40.0	206.5	96	U0
1	167	146	44.0	25	90	50.0	215.0	96	U0
1 1/4	167	146	55.0	29	110	61.0	230.0	96	U0
1 1/2	167	146	61.5	30	120	73.0	237.5	96	R0
2	167	146	73.0	43	140	88.0	262.0	96	R0
2 1/2	168	200	85.0	57	165	113.0	342.0	105	R1
3	168	200	94.5	68	188	135.0	362.5	105	R1
4	200	247	116.0	83	225	166.0	446.0	216	R2

SPECIFICATIONS			
VALVE		ELECTRIC ACTUATOR	
BODY	Full Bore Nickel plated brass	PROTECTION RATING	IP65 (Weatherproof)
SEATS	PTFE	VOLTAGES	12, 24DC 24, 110, 240 AC
SEALS	Flouroelastomer	MANUAL OVERRIDE	Standard Across Range
ENDS	BSPP	VOLT FREE CONTACTS	Standard Across Range(2-off)
 <div style="border: 1px solid red; padding: 2px; font-size: 8px; color: red; display: inline-block;"> All Dimensions In mm. Uncontrolled Copy, Not Subject To Automatic Update E&OE </div>		VISUAL INDICATOR	Standard Across Range
		DUTY RATING	35%
		ON POWER FAILURE	Stays put
		CONNECTION	All external by Din plug

F.B. BRASS BALL VALVE WITH MODULATING ACTUATOR

J+J
ACTUATORS

Drawn By
MRG

Chk
DC

File Name
1105

Scale
NTS

Dwg No. 1105

Revision
1

Sheet
1/1

Date
06/01/01