


SIZE	A	B	C	D	F	G	H	W	ACT.
1/4									
3/8									
1/2	168	146	32.7	19.5	77		198.2	96	R0
3/4	168	146	41.5	24.0	87		211.5	96	R0
1	168	146	47.0	30.0	105		223.0	96	R0
1 1/4	168	200	59.5	36.0	123		295.5	105	R1
1 1/2	168	200	73.9	43.0	139		316.9	105	R1
2	168	200	85.0	55.5	166		340.5	105	R1

SPECIFICATIONS				
VALVE		ELECTRIC ACTUATOR		
BODY	Nickel plated brass	PROTECTION RATING	IP65 (Weatherproof)	
SEATS	PTFE	VOLTAGES	12, 24DC 24, 110, 240 AC	
SEALS	Viton	MANUAL OVERRIDE	Standard Across Range	
ENDS	BSP	VOLT FREE CONTACTS	Standard Across Range(2-off)	
 <div style="border: 1px solid red; padding: 2px; font-size: 8px; color: red; display: inline-block;">           All Dimensions In mm.            Uncontrolled Copy,            Not Subject To            Automatic Update            E&amp;OE         </div>		VISUAL INDICATOR	Standard Across Range	
			DUTY RATING	35%
			ON POWER FAILURE	Stays put
			CONNECTION	All external by Din plug

## F.B. BRASS 3-WAY BALL VALVE WITH MODULATING ACTUATOR

**J+J**  
ACTUATORS

Drawn By  
MRG

Chk  
DC

File Name  
1305

Scale  
NTS

Dwg No. 1305

Revision  
1

Sheet  
1/1

Date  
06/01/01