


SIZE	A	B	C	D	E	F	G	H	W	ACT.
1/2	167	147	28	28	50	108	81	253	104	J2-20DPS
3/4	167	147	33	33	50	128	95	263	104	J2-20DPS
1	167	147	37	37	50	144	108	271	104	J2-20DPS
1 1/4	167	147	43	43	50	173	129	283	104	J2-20DPS
1 1/2	167	147	52	52	50	197	148	301	104	J2-20DPS
2	167	147	60	60	50	243	180	317	104	J2-20DPS

SPECIFICATIONS			
VALVE		ELECTRIC ACTUATOR	
BODY	PVC	PROTECTION RATING	IP65 (Weatherproof)
SEATS	PTFE	VOLTAGES	12V DC to 240V AC
SEALS	EPDM (Viton option)	MANUAL OVERRIDE	Standard Across Range
ENDS	Imp or metric plain socket/ bsp	VOLT FREE CONTACTS	Standard Across Range (2-off)
 <div style="border: 1px solid black; padding: 2px; font-size: 8px;">           All Dimensions In mm.            Uncontrolled Copy,            Not Subject To            Automatic Update            E&amp;OE         </div>		VISUAL INDICATOR	Standard Across Range
		DUTY RATING	100%
		ON POWER FAILURE	Stays put
		CONNECTION	All external by Din plug

## 3-WAY P.V.C. BALL VALVE WITH MODULATING ACTUATOR & KIT

### MODULATING ACTUATOR

Drawn By  
MRG

Chk  
DC

File Name  
3315J2

Scale  
NTS

Dwg No.

3315J2

Revision  
1

Sheet  
1/1

Date  
01/05/02